

TEST REPORT

No.: SHCCM130100020

Date: Jan. 09, 2013

Page: 1 of 2

DOWSENG LIMITED

XIYOU TOWN, LAIZHOU CITY, SHANDONG PROVINCE, CHINA

The following sample(s) was/ were submitted and identified on behalf of the client as:

Sample Name : FLOOR / PEDESTAL / FASTENER

Sample Number : SHCCM130100020 Test Required : Ultimate loading

Test Method : CISCA
Product specification : SC800B

Manufacturer : DOWSENG LIMITED

Date of Receipt : Jan. 04, 2013

Test Period : Jan. 04, 2013 to Jan. 09, 2013

Test result(s) : For further details, please refer to the following page(s)

******* To be continued******

Signed for SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

Sally Xie

Authorized signatory

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.
Itm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of iability is taken information contained hereon reflects the Company's findings at the time of its just a subject of the inition of the inition of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all the vights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. The interview of the first of the company. It is not that the prior of falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

If the provided it is a subject to the first of the subject is a subject to the fullest extent of the law.



TEST REPORT

No.: SHCCM130100020

Date: Jan. 09, 2013

Page: 2 of 2

Test Conducted: CISCA Recommended test procedures for access floors (2007) Section 2 Ultimate loading Test Results:

No.	Location of indentor	Ultimate load (N)
Panel 1	At the centre of the panel	9986
Panel 2	At the midpoint of panel edge	9541
Panel 3	At the point along a diagonal 70 mm beyond the edge of the pedestal head on the panel	13128

Height of system: 187mm.

Statement: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

****** End of report ******

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm, and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, in the subject of the